

IN THE CLAIMS:

Please amend the claims as follows:

1. (Original) Projector arrangement, comprising:
 - a projector unit (3) having an objective unit (4) for optically projecting images, in particular on an external screen (20), and
 - an objective cover unit (6) for covering a light exit portion (4e) or light exit surface (4e) of said objective unit (4) in a standby, pause, non-projecting mode and/or non-operation mode of said projector arrangement (1),

characterized in

that said objective cover unit (6) is adapted to serve and/or to function as a support or bearing unit (8) for supporting said projector unit (3), in particular on an external operation surface (100), in an operation mode of said projector arrangement (1).

2. (Original) Projector arrangement according to claim 1,

wherein said objective cover unit (6) and/or said projector unit (3) are formed and/or are adapted to allow a plurality of locations (P2, P3, P4) and/or portions (P2, P3, P4) of or on said projector unit (3) to be rested on said objective cover unit (6) when said projector unit (3) is supported by said objective cover unit (6) as said support or bearing unit (8) in said operation mode of said projector arrangement (1).

3. (Original) Projector arrangement according to claim 2,

wherein each of said locations (P2, P3, P4) and/or portions (P2, P3, P4) of or on said projector unit (3) are chosen to be assigned to and/or to realize a distinct position and/or orientation of said projector arrangement (1) and in particular of its objective unit (4) when said projector unit (3) is

supported by said objective cover unit (6) as said support or bearing unit (8) in said operation mode of said projector arrangement (1).

4. (Original) Projector arrangement,

comprising a projector unit (3) having an objective unit (4) for optically projecting images, in particular on an external screen (20),

characterized in

- that a surface region (2a) is provided having a plurality of locations (P2, P3, P4) and/or portions (P2, P3, P4) being adapted for directly or indirectly resting on, in particular an external operation or working surface (100), in an operation mode or projecting mode of said projector arrangement (1) and
- that each of said locations (P2, P3, P4) and/or portions (P2, P3, P4) of or on said projector unit (3) are chosen to be assigned to and/or to realize a distinct position and/or orientation of said projector arrangement (1) and in particular of its objective unit (4) in said operation mode or projecting mode of said projector arrangement (1).

5. (Original) Projector arrangement according to claim 4,

wherein fixing means is/are provided for detachably fixing said projector arrangement (1) and in particular said projector unit (3) in each of said locations (P2, P3, P4) and/or portions (P2, P3, P4) and in particular in each of said distinct positions and/or orientations, when resting in or on a respective location (P2, P3, P4) and/or portion (P2, P3, P4).

6. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims 4 or 5~~ claim 4,

- wherein an objective cover unit (6) for covering a light exit portion (4e) or light exit surface (4e) of said objective unit (4) in a standby, pause, non-projecting mode and/or non-operation mode of said projector arrangement (1), and
- wherein that said objective cover unit (6) is adapted to serve and/or to function as a support or bearing unit (8) for supporting said projector unit (3) and/or as said fixing means (8), in particular on an external operation surface (100), in an operation mode of said projector arrangement (1).

7. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims 2 to 6~~ claim 2,

wherein each of said locations (P2, P3, P4) and/or portions (P2, P3, P4) of or on said projector unit (3) are chosen to be assigned to and/or to realize distinct – vertical and/or horizontal – projection angles ($\alpha_2, \alpha_3, \alpha_4$) or inclination angles ($\alpha_2, \alpha_3, \alpha_4$) of said projector arrangement (1) and in particular of its objective unit (4) when said projector unit (3) is supported by said objective cover unit (6) as said support or bearing unit (8) in said operation mode of said projector arrangement (1) and/or in particular with respect to a horizontal plane of an external operating surface (100) and/or with respect to said external screen (20).

8. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims 2 to 7~~ claim 2,

wherein said objective cover unit (6) and/or said projector unit (3) are formed and/or are adapted to provide a continuously distributed plurality of said locations/portions (P2, P3, P4), positions/orientations and/or projection angles ($\alpha_2, \alpha_3, \alpha_4$) or inclination angles ($\alpha_2, \alpha_3, \alpha_4$).

9. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims~~ claim 1,

wherein said projector unit (3) comprises a base portion (2) having a surface (2a), in particular as said surface region (2a) of said projector unit, at least a part of which being continuously and/or smoothly curved in an at least local convex manner,

- in particular so as to realize said plurality of said locations/portions (P2, P3, P4), positions/orientations and/or projection angles (α_2 , α_3 , α_4) or inclination angles (α_2 , α_3 , α_4), in particular on its surface (2a), and/or
- in particular so as to enable in said operation mode of said projector arrangement (1) a resting or supporting of said projector unit (3) on said support or bearing unit (8).

10. (Original) Projector arrangement according to claim 9,

wherein said base portion (2) has at least in part - when cross sectionally viewed - an at least partial circular, elliptical, and/or parabolic shape.

11. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims 9 or 10~~ claim 9,

wherein said base portion (2) has at least in part a spherical, ellipsoidal, paraboloidal and/or cylindrical shape.

12. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims 9 to 11~~ claim 9,

wherein said base portion (2) is essentially formed as a hemisphere or hemi-cylinder or as a part thereof.

13. (Currently Amended) Projector arrangement according to ~~any one of the preceding claims~~ claim 1,

wherein said objective cover unit (6) is formed as a detachable cap for said objective unit (4).

14. (Currently Amended) Projector arrangement according to ~~any one of the preceding~~
~~claims~~ claim 1,

wherein said objective cover unit (6) comprises:

- a first or inner base surface (6o) adapted to face said light exit portion (4e) or light exit surface (4e) of said objective unit (4) in said standby, pause, non-projecting and/or non-operating mode and to face said projector unit (3) and in particular said base portion (2) further in particular its surface (2a) in said operation mode of said projector arrangement (1), and
- a second or outer base surface (6b) situated opposite said first or inner base surface (6i) and therefore situated opposite from said light exit portion or said light exit surface (4e) of said objective unit (4) in said standby, pause, non-projecting, and/or non-operating mode and opposite said base portion (2) and/or said surface (2a) thereof in said operation mode and which is in particular adapted to face and rest on said external operating surface (100) in said operation mode.

15. (Original) Projector arrangement according to claim 14,

wherein said objective cover unit (6) comprises a rim portion (6r), in particular provided on the periphery of said first or inner base surface (6o) and projecting away from said first or inner base surface (6o), in particular essentially in the direction of the inner base surface's (6o) normal (n6), thereby forming abutment surfaces (6u) adapted to support or to have rested on said projector unit (3), in particular said base portion (2) and in particular its surface (2a) in said operation mode of said projector arrangement (1).

16. (Currently Amended) Projector arrangement according to ~~any one of the preceding~~
~~claims~~ claim 1,

wherein said objective cover unit (6) as said support or bearing unit (8) and in particular its rim portion (6r) and/or said abutment surfaces (6u) and/or said projector unit (6r) and in particular its base portion (2) are formed and adapted to realized one or an arbitrary combination or plurality of the following aspects:

- cooperation and/or engaging of respective shapes and/or surfaces,
- frictional interaction forces between each other,
- stable and/or equilibrated support of said projector unit.

17. (Currently Amended) Projector arrangement according to ~~any one of the preceding~~ claims claim 1,

wherein said projector unit (3) and in particular its base portion (2) have a shape and/or a mass distribution so as to ensure to be supported by said support or bearing unit (8) in mass or gravitational equilibrium.

18. (Currently Amended) Projector arrangement according to ~~any one of the preceding~~ claims claim 1,

wherein said objective cover unit (6) and in particular its rim portion (6r) comprise position holding or fixing elements for ensuring an essentially fixed positioning of the supported and rested projector unit (3) in said operation mode.

19. (New) Projector arrangement according to claim 4,

wherein each of said locations (P2, P3, P4) and/or portions (P2, P3, P4) of or on said projector unit (3) are chosen to be assigned to and/or to realize distinct – vertical and/or horizontal – projection angles ($\alpha_2, \alpha_3, \alpha_4$) or inclination angles ($\alpha_2, \alpha_3, \alpha_4$) of said projector arrangement (1) and in particular of its objective unit (4) when said projector unit (3) is supported by said objective cover unit (6) as said support or bearing unit (8) in said operation mode of said

projector arrangement (1) and/or in particular with respect to a horizontal plane of an external operating surface (100) and/or with respect to said external screen (20).

20. (New) Projector arrangement according to claim 4,

wherein said objective cover unit (6) and/or said projector unit (3) are formed and/or are adapted to provide a continuously distributed plurality of said locations/portions (P2, P3, P4), positions/orientations and/or projection angles (α_2 , α_3 , α_4) or inclination angles (α_2 , α_3 , α_4).

21. (New) Projector arrangement according to claim 4,

wherein said projector unit (3) comprises a base portion (2) having a surface (2a), in particular as said surface region (2a) of said projector unit, at least a part of which being continuously and/or smoothly curved in an at least local convex manner,

- in particular so as to realize said plurality of said locations/portions (P2, P3, P4), positions/orientations and/or projection angles (α_2 , α_3 , α_4) or inclination angles (α_2 , α_3 , α_4), in particular on its surface (2a), and/or
- in particular so as to enable in said operation mode of said projector arrangement (1) a resting or supporting of said projector unit (3) on said support or bearing unit (8).

22. (New) Projector arrangement according to claim 4,

wherein said objective cover unit (6) is formed as a detachable cap for said objective unit (4).

23. (New) Projector arrangement according to claim 4,

wherein said objective cover unit (6) comprises:

- a first or inner base surface (6o) adapted to face said light exit portion (4e) or light exit surface (4e) of said objective unit (4) in said standby, pause, non-projecting and/or non-operating mode and to face said projector unit (3) and in particular said base portion (2)

further in particular ist surface (2a) in said operation mode of said projector arrangement (1), and

- a second or outer base surface (6b) situated opposite said first or inner base surface (6i) and therefore situated opposite from said light exit portion or said light exit surface (4e) of said objective unit (4) in said standby, pause, non-projecting, and/or non-operating mode and opposite said base portion (2) and/or said surface (2a) thereof in said operation mode and which is in particular adapted to face and rest on said external operating surface (100) in said operation mode.

24. (New) Projector arrangement according to claim 4, wherein said objective cover unit (6) as said support or bearing unit (8) and in particular its rim portion (6r) and/or said abutment surfaces (6u) and/or said projector unit (6r) and in particular its base portion (2) are formed and adapted to realized one or an arbitrary combination or plurality of the following aspects:

- cooperation and/or engaging of respective shapes and/or surfaces,
- frictional interaction forces between each other,
- stable and/or equilibrated support of said projector unit.

25. (New) Projector arrangement according to claim 4, wherein said projector unit (3) and in particular its base portion (2) have a shape and/or a mass distribution so as to ensure to be supported by said support or bearing unit (8) in mass or gravitational equilibrium.

26. (New) Projector arrangement according to claim 4,

wherein said objective cover unit (6) and in particular its rim portion (6r) comprise position holding or fixing elements for ensuring an essentially fixed positioning of the supported and rested projector unit (3) in said operation mode.